# **TECO MOTOR VIBRATION VB-100**

## IP65 Industrial Grade Stand-alone Motor Vibration Meter

TECO'S VB-100 motor vibration meter is a cutting-edge, battery-powered, stand-alone product, revolutionising the way you monitor motor vibrations. It combines a highly sensitive MEMS vibration sensor with a user-friendly digital display, offering unparalleled convenience simplicity and effectiveness.

With the VB-100, there's no need for complicated setups involving gateways, wifi, or other vibration measurement platforms.

Simply press the button, and the built-in LED display will provide you with real-time, single-axis motor vibration velocity.



Understanding and monitoring your motor's health has never been easier! Just scan the QR code on the unit to access a detailed table outlining the health index and performance insights.

VB-100 is designed for quick mounting and effortless viewing, ensuring seamless integration into your motor monitoring and maintenance routine.

With TECO's VB-100 Motor Vibration Meter, take charge of your electric motor's health like never before.

# **SPECIFICATIONS**

- RMS vibration (velocity) measurement range 0~99 mm/s
- Sensitivity error 5%(max) @100Hz
- Frequency response 10~1000 Hz for ISO10816
- Temperature error range ±0.01%/°C
- Nonlinearity ±0.2%

- Cross-axis sensitivity ±1.0% typical, ±3.5% max
- Working temperature Body: -40 ~85 °C
- Lithium Battery: -40 ~70 °C (CR2)
- Shock limit 20,000g
- Noise 70µg/√Hz

## **FEATURES**

- 7-Segment LED Display
- IP65 rated
- · Vibration data measurement and display; velocity RMS (mm/s)
- Vibration measurement, smart display: (1) RMS vibration value; (2) Alarm (LED flashing); (3) Vibration health index (H1 to H9, H9 being the healthiest reading)
- Pressing the button activates the screen for 20 seconds, providing instantaneous vibration velocity RMS followed by the health index
- · Compact size is suitable for motors of frame sizes 132 to 250
- Adhesive installation method.



# **TECO MOTOR VIBRATION VB-100**


## IP65 Industrial Grade Stand-alone Motor Vibration Meter

TECO provides two specific models:

- 1. VB-100A (curved base) suitable for motor frame size up to 132
- 2. VB-100C (flat bottom) suitable for motor frame sizes from 160 to 250


#### **VB-100A**


59 x 31 x 22.3mm



## VB-100C

59 x 29 x 22.3mm





#### **Real-Time Monitoring Made Easy - Health Index**

- 1. When your motor is up and running, a simple press of the button next to the LCD display on the VB-100 allows you to instantly access real-time motor vibration velocity readings and health index
- 2. Stay informed about your motor's performance, all at your fingertips
- 3. For a comprehensive view of the Vibration Health Index, just scan the QR Code on the battery cover
- 4. The index is divided into 9 levels, with H9 indicating the healthiest reading.
- 5. Easily and quality assess your motor's condition and make data-driven decisions.



### Head Office Australia - NSW

**TECO Australia Pty Limited** 335-337 Woodpark Road, Smithfield NSW 2164

02 9765 8118 sales.nsw@teco.com.au

### VIC/TAS/SA

**TECO Australia Pty Limited** 16 Longstaff Road, Bayswater VIC 3153

03 9720 4411 vicsales@teco.com.au

### WA

**TECO Australia Pty Limited** 18 Hazelhurst Street, Kewdale WA 6105

08 9479 4879 sales.wa@teco.com.au

### QLD

**TECO Australia Pty Limited** 50 Murdoch Circuit, Acacia Ridge QLD 4110

07 3373 9600 sales.qld@teco.com.au

### New Zealand

**TECO New Zealand Ltd**Unit 3, 477 Great South
Road, Penrose, Auckland

+ 64 9 526 8480 sales@teco.co.nz



