



DATASHEET

Te3 CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		1.1
VOLTAGE	(V)	240
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		2
FRAME		80
SPEED		
SYNCHRONOUS	(rpm)	3000
FULL LOAD	(rpm)	2840
CURRENT		
FULL LOAD	(Amps)	3.89
LOCKED ROTOR	%	720
TORQUE		
FULL LOAD TORQUE	(Nm)	3.68
STARTING TORQUE	%	220
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	230
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.0013
EFFICIENCY		
100% LOAD	%	83
75% LOAD	%	84.8
50% LOAD	%	83.4
POWER FACTOR		
100% LOAD	%	0.83
75% LOAD	%	0.76
50% LOAD	%	0.64
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	20
BEARINGS		
DRIVE END		6204 ZZ
NON DRIVE END		6204 ZZ
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	59
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C