



DATASHEET

Te3 CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		11
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		8
FRAME		180L
SPEED		
SYNCHRONOUS	(rpm)	750
FULL LOAD	(rpm)	730
CURRENT		
FULL LOAD	(Amps)	22.7
LOCKED ROTOR	%	660
TORQUE		
FULL LOAD TORQUE	(Nm)	144
STARTING TORQUE	%	200
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	200
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.214
EFFICIENCY		
100% LOAD	%	88.8
75% LOAD	%	89
50% LOAD	%	88.6
POWER FACTOR		
100% LOAD	%	0.76
75% LOAD	%	0.72
50% LOAD	%	0.62
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	184
BEARINGS		
DRIVE END		6311
NON DRIVE END		6211
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	62
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C