



DATASHEET

Te3 CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		22
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		6
FRAME		200L
SPEED		
SYNCHRONOUS	(rpm)	1000
FULL LOAD	(rpm)	980
CURRENT		
FULL LOAD	(Amps)	40.2
LOCKED ROTOR	%	750
TORQUE		
FULL LOAD TORQUE	(Nm)	214
STARTING TORQUE	%	210
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	210
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.37
EFFICIENCY		
100% LOAD	%	92.2
75% LOAD	%	92
50% LOAD	%	91.3
POWER FACTOR		
100% LOAD	%	0.81
75% LOAD	%	0.8
50% LOAD	%	0.74
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	258
BEARINGS		
DRIVE END		6312
NON DRIVE END		6212
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	68
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C