



DATASHEET

Te3 CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		37
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		2
FRAME		200L
SPEED		
SYNCHRONOUS	(rpm)	3000
FULL LOAD	(rpm)	2955
CURRENT		
FULL LOAD	(Amps)	61.3
LOCKED ROTOR	%	750
TORQUE		
FULL LOAD TORQUE	(Nm)	120
STARTING TORQUE	%	200
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	230
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.17
EFFICIENCY		
100% LOAD	%	93.8
75% LOAD	%	93.4
50% LOAD	%	92.3
POWER FACTOR		
100% LOAD	%	0.89
75% LOAD	%	0.89
50% LOAD	%	0.85
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	258
BEARINGS		
DRIVE END		6212
NON DRIVE END		6212
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	84
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C