



DATASHEET

Te3 CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		132
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		315M/L-468
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1484
CURRENT		
FULL LOAD	(Amps)	216
LOCKED ROTOR	%	690
TORQUE		
FULL LOAD TORQUE	(Nm)	847
STARTING TORQUE	%	210
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	220
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	2.58
EFFICIENCY		
100% LOAD	%	95.7
75% LOAD	%	95.5
50% LOAD	%	94.7
POWER FACTOR		
100% LOAD	%	0.89
75% LOAD	%	0.88
50% LOAD	%	0.84
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	1100
BEARINGS		
DRIVE END		6319
NON DRIVE END		6319
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	85
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C