



DATASHEET

Te3 CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		250
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		6
FRAME		355M/L-68
SPEED		
SYNCHRONOUS	(rpm)	1000
FULL LOAD	(rpm)	990
CURRENT		
FULL LOAD	(Amps)	413
LOCKED ROTOR	%	670
TORQUE		
FULL LOAD TORQUE	(Nm)	2412
STARTING TORQUE	%	190
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	220
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	10.8
EFFICIENCY		
100% LOAD	%	95.9
75% LOAD	%	95.9
50% LOAD	%	95.2
POWER FACTOR		
100% LOAD	%	0.87
75% LOAD	%	0.86
50% LOAD	%	0.81
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	1850
BEARINGS		
DRIVE END		6322
NON DRIVE END		6322
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	75
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C