



DATASHEET

Te3 Severe Duty CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 Severe Duty CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		0.75
VOLTAGE	(V)	240
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		80
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1400
CURRENT		
FULL LOAD	(Amps)	2.94
LOCKED ROTOR	%	660
TORQUE		
FULL LOAD TORQUE	(Nm)	5
STARTING TORQUE	%	230
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	220
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.002
EFFICIENCY		
100% LOAD	%	82.9
75% LOAD	%	82.9
50% LOAD	%	79.3
POWER FACTOR		
100% LOAD	%	75
75% LOAD	%	66
50% LOAD	%	53
INSULATION CLASS		H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	21
BEARINGS		
DRIVE END		6204 ZZ
NON DRIVE END		6204 ZZ
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	50
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C