



DATASHEET

Te3 Severe Duty CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 Severe Duty CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		3
VOLTAGE	(V)	240
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		100L
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1430
CURRENT		
FULL LOAD	(Amps)	10.2
LOCKED ROTOR	%	740
TORQUE		
FULL LOAD TORQUE	(Nm)	19.8
STARTING TORQUE	%	230
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	230
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.0093
EFFICIENCY		
100% LOAD	%	87.9
75% LOAD	%	87.1
50% LOAD	%	94.6
POWER FACTOR		
100% LOAD	%	82
75% LOAD	%	71
50% LOAD	%	59
INSULATION CLASS		H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	44
BEARINGS		
DRIVE END		6206 ZZ
NON DRIVE END		6206 ZZ
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	56
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C