



DATASHEET

Te3 Severe Duty CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 Severe Duty CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		22
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		2
FRAME		180M
SPEED		
SYNCHRONOUS	(rpm)	3000
FULL LOAD	(rpm)	2950
CURRENT		
FULL LOAD	(Amps)	36.9
LOCKED ROTOR	%	750
TORQUE		
FULL LOAD TORQUE	(Nm)	71.6
STARTING TORQUE	%	220
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	230
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.08
EFFICIENCY		
100% LOAD	%	92.8
75% LOAD	%	92.4
50% LOAD	%	91.2
POWER FACTOR		
100% LOAD	%	89
75% LOAD	%	89
50% LOAD	%	84
INSULATION CLASS		H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	176
BEARINGS		
DRIVE END		6211
NON DRIVE END		6211
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	81
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C