



DATASHEET

Te3 Severe Duty CAST IRON FRAME TO 500KW

MOTOR SERIES	Te3 Severe Duty CAST IRON FRAME TO 500KW	
START METHOD		DIRECT ON LINE
KW RATING		160
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		6
FRAME		355M/L-68
SPEED		
SYNCHRONOUS	(rpm)	1000
FULL LOAD	(rpm)	991
CURRENT		
FULL LOAD	(Amps)	269
LOCKED ROTOR	%	670
TORQUE		
FULL LOAD TORQUE	(Nm)	1544
STARTING TORQUE	%	190
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	200
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	7.44
EFFICIENCY		
100% LOAD	%	95.7
75% LOAD	%	95.8
50% LOAD	%	95.4
POWER FACTOR		
100% LOAD	%	86
75% LOAD	%	86
50% LOAD	%	80
INSULATION CLASS		H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	1650
BEARINGS		
DRIVE END		6322
NON DRIVE END		6322
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	84
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C