



DATASHEET

TECO IE3 FLAMEPROOF (EXD) TEFC

MOTOR SERIES	TECO IE3 FLAMEPROOF (EXD) TEFC	
START METHOD		DIRECT ON LINE
KW RATING		55
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		250SC-4P
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1485
CURRENT		
FULL LOAD	(Amps)	93.7
LOCKED ROTOR	%	736
TORQUE		
FULL LOAD TORQUE	(Nm)	353
STARTING TORQUE	%	220
MINIMUM TORQUE	%	245
BREAKDOWN TORQUE	%	275
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.9778
EFFICIENCY		
100% LOAD	%	95
75% LOAD	%	95
50% LOAD	%	95
POWER FACTOR		
100% LOAD	%	86
75% LOAD	%	83.5
50% LOAD	%	76.5
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		56
WEIGHT OF MOTOR	kgs	609
BEARINGS		
DRIVE END		6317 C3
NON DRIVE END		6313 C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	70
DESIGN STANDARD		BS4999, IEC60034, IEC60079-1:2014, IEC60079-0:2011
CERTIFICATION		Ex db, IIB, T4, Gb and Ex db, I, Mb both -20°C < Tamb < 55°C
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C