



DATASHEET

TECO FLAMEPROOF TEFC

MOTOR SERIES	TECO FLAMEPROOF TEFC	
START METHOD		DIRECT ON LINE
KW RATING		1.5
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		90L
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1430
CURRENT		
FULL LOAD	(Amps)	3.26
LOCKED ROTOR	%	706
TORQUE		
FULL LOAD TORQUE	(Nm)	9.9
STARTING TORQUE	%	300
MINIMUM TORQUE	%	240
BREAKDOWN TORQUE	%	310
ROTOR INERTIA (J = GD ² /4)	(Kgm ²)	0.00575
EFFICIENCY		
100% LOAD	%	85
75% LOAD	%	85
50% LOAD	%	83
POWER FACTOR		
100% LOAD	%	75
75% LOAD	%	66.5
50% LOAD	%	53
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	35
BEARINGS		
DRIVE END		6205 ZZ C3
NON DRIVE END		6205 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	47
DESIGN STANDARD		AS1359, BS4999, IEC60079-0:2004, IEC60079-1:2007, IEC60079-7:2006
CERTIFICATION		Ex de, Zone 1, IIC, T4 (T3 on VSD) 50°Camb
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C