



DATASHEET

TECO FLAMEPROOF TEFC

MOTOR SERIES	TECO FLAMEPROOF TEFC	
START METHOD		DIRECT ON LINE
KW RATING		15
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		160L
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1460
CURRENT		
FULL LOAD	(Amps)	25.4
LOCKED ROTOR	%	728
TORQUE		
FULL LOAD TORQUE	(Nm)	97.4
STARTING TORQUE	%	230
MINIMUM TORQUE	%	180
BREAKDOWN TORQUE	%	270
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.1155
EFFICIENCY		
100% LOAD	%	93
75% LOAD	%	93
50% LOAD	%	92.5
POWER FACTOR		
100% LOAD	%	88
75% LOAD	%	84.5
50% LOAD	%	76.5
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	182
BEARINGS		
DRIVE END		6309 ZZ C3
NON DRIVE END		6307 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	56
DESIGN STANDARD		AS1359, BS4999, IEC60079-0:2004, IEC60079-1:2007, IEC60079-7:2006
CERTIFICATION		Ex de, Zone 1, IIC, T4 (T3 on VSD) 50°Camb
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C