



DATASHEET

TECO OPEN DRIP POOF ODP

MOTOR SERIES	TECO OPEN DRIP POOF ODP	
START METHOD		DIRECT ON LINE
KW RATING		11
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		C160M
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1465
CURRENT		
FULL LOAD	(Amps)	21
LOCKED ROTOR	%	667
TORQUE		
FULL LOAD TORQUE	(Nm)	71.70648464
STARTING TORQUE	%	210
MINIMUM TORQUE	%	170
BREAKDOWN TORQUE	%	260
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.0743
EFFICIENCY		
100% LOAD	%	91
75% LOAD	%	91
50% LOAD	%	91
POWER FACTOR		
100% LOAD	%	80
75% LOAD	%	76
50% LOAD	%	66
INSULATION CLASS		F
ENCLOSURE TYPE		ODP
IP RATING		23
WEIGHT OF MOTOR	kgs	105
BEARINGS		
DRIVE END		6310 ZZ
NON DRIVE END		6309 ZZ
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C