



DATASHEET

3-PHASE MEDIUM VOLTAGE HIGH EFFICIENCY SCIM

MOTOR SERIES	3-PHASE MEDIUM VOLTAGE HIGH EFFICIENCY SCIM	
START METHOD		DIRECT ONLINE
KW RATING		250
VOLTAGE	(V)	3300
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		2
FRAME		315DA
SPEED		
SYNCHRONOUS	(rpm)	3000
FULL LOAD	(rpm)	2981
CURRENT		
FULL LOAD	(Amps)	52.36
LOCKED ROTOR	%	705
TORQUE		
FULL LOAD TORQUE	(Nm)	800
STARTING TORQUE	%	110
MINIMUM TORQUE	%	100
BREAKDOWN TORQUE	%	220
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	11.4
EFFICIENCY		
100% LOAD	%	94.9
75% LOAD	%	94.7
50% LOAD	%	93.7
POWER FACTOR		
100% LOAD	%	88
75% LOAD	%	85.2
50% LOAD	%	77.7
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	1890
BEARINGS		
DRIVE END		6315C3
NON DRIVE END		6315C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	80
DESIGN STANDARD		IEC60034
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C