



DATASHEET

3-PHASE MEDIUM VOLTAGE HIGH EFFICIENCY SCIM

MOTOR SERIES	3-PHASE MEDIUM VOLTAGE HIGH EFFICIENCY SCIM	
START METHOD		DIRECT ONLINE
KW RATING		800
VOLTAGE	(V)	3300
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		400DB*
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1488
CURRENT		
FULL LOAD	(Amps)	171.12
LOCKED ROTOR	%	640
TORQUE		
FULL LOAD TORQUE	(Nm)	5120
STARTING TORQUE	%	130
MINIMUM TORQUE	%	120
BREAKDOWN TORQUE	%	220
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	99.1
EFFICIENCY		
100% LOAD	%	95.9
75% LOAD	%	95.9
50% LOAD	%	95.5
POWER FACTOR		
100% LOAD	%	85.1
75% LOAD	%	81
50% LOAD	%	72.3
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	4310
BEARINGS		
DRIVE END		6226
NON DRIVE END		6222
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	80
DESIGN STANDARD		IEC60034
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C