



# DATASHEET

## 3-PHASE MEDIUM VOLTAGE HIGH EFFICIENCY SCIM

<b>MOTOR SERIES</b>	3-PHASE MEDIUM VOLTAGE HIGH EFFICIENCY SCIM	
<b>START METHOD</b>		DIRECT ONLINE
<b>KW RATING</b>		220
<b>VOLTAGE</b>	(V)	3300
<b>PHASES</b>		3
<b>FREQUENCY</b>	(Hz)	50
<b>NO OF POLES</b>		8
<b>FRAME</b>		355CB
<b>SPEED</b>		
SYNCHRONOUS	(rpm)	750
FULL LOAD	(rpm)	743
<b>CURRENT</b>		
FULL LOAD	(Amps)	52.85
LOCKED ROTOR	%	630
<b>TORQUE</b>		
FULL LOAD TORQUE	(Nm)	2875
STARTING TORQUE	%	94
MINIMUM TORQUE	%	89
BREAKDOWN TORQUE	%	202
<b>ROTOR INERTIA (J = GD<sup>2</sup>/4)</b>	(Kgm <sup>2</sup> )	69
<b>EFFICIENCY</b>		
100% LOAD	%	93.9
75% LOAD	%	94.1
50% LOAD	%	93.7
<b>POWER FACTOR</b>		
100% LOAD	%	78.9
75% LOAD	%	73.5
50% LOAD	%	62.9
<b>INSULATION CLASS</b>		F
<b>ENCLOSURE TYPE</b>		TEFC
<b>IP RATING</b>		55
<b>WEIGHT OF MOTOR</b>	kgs	2450
<b>BEARINGS</b>		
DRIVE END		6222
NON DRIVE END		6220
<b>NO LOAD SOUND PRESSURE LEVEL @ 1M</b>	dbA	75
<b>DESIGN STANDARD</b>		IEC60034
<b>CERTIFICATION</b>		
<b>TEMPERATURE RISE ABOVE AMBIENT</b>		< 80 DEG C