



DATASHEET

MAXALLOY THREE PHASE ALLOY FRAME TEFC

MOTOR SERIES	MAXALLOY THREE PHASE ALLOY FRAME TEFC	
START METHOD		DIRECT ON LINE
KW RATING		0.25
VOLTAGE	(V)	240
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		6
FRAME		71
SPEED		
SYNCHRONOUS	(rpm)	1000
FULL LOAD	(rpm)	850
CURRENT		
FULL LOAD	(Amps)	1.5
LOCKED ROTOR	%	4
TORQUE		
FULL LOAD TORQUE	(Nm)	2.81
STARTING TORQUE	%	240
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	240
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	
EFFICIENCY		
100% LOAD	%	67
75% LOAD	%	
50% LOAD	%	
POWER FACTOR		
100% LOAD	%	68
75% LOAD	%	
50% LOAD	%	
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	
BEARINGS		
DRIVE END		6202 ZZ
NON DRIVE END		6202 ZZ
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C