



DATASHEET

MAXALLOY THREE PHASE ALLOY FRAME TEFC

MOTOR SERIES	MAXALLOY THREE PHASE ALLOY FRAME TEFC	
START METHOD		DIRECT ON LINE
KW RATING		3
VOLTAGE	(V)	240
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		6
FRAME		132S
SPEED		
SYNCHRONOUS	(rpm)	1000
FULL LOAD	(rpm)	960
CURRENT		
FULL LOAD	(Amps)	11.8
LOCKED ROTOR	%	5.75
TORQUE		
FULL LOAD TORQUE	(Nm)	29.84
STARTING TORQUE	%	203
MINIMUM TORQUE	%	
BREAKDOWN TORQUE	%	210
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	
EFFICIENCY		
100% LOAD	%	83.5
75% LOAD	%	
50% LOAD	%	
POWER FACTOR		
100% LOAD	%	74
75% LOAD	%	
50% LOAD	%	
INSULATION CLASS		F
ENCLOSURE TYPE		TEFC
IP RATING		55
WEIGHT OF MOTOR	kgs	
BEARINGS		
DRIVE END		6308 ZZ
NON DRIVE END		6306 ZZ
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C