


DATA SHEET ~ TECO MAXe3™ PREMIUM SEVERE DUTY - MEPS HIGH EFFICIENCY	
Type	Squirrel Cage Induction Motor ~ TEFC
Input Supply	415Volts 50Hz 3 Phase
Degree of Protection	IP66 Complete with Porous Drain Plugs
Mounting Arrangments	IM1001 B3 / IM3001 B5 / IM2001 B35
Cooling Class	IC411
Insulation	Class 'F' 155°C
Temperature Rise	≤80°C
Ambient Condition	40°C (TECO can accept up to 55°C ambient as standard)
Altitude	Less than 1000 Metres above sea level
Application	Direct Coupled
Starting Method	DOL, Soft Starter or VVVF Duty (Subject to load demand)
Service Factor	1.0 p.u @ Class B Temp. rise - 1.15 p.u @ Class F Temp. rise
Rotation	Bi Directional - Low Noise
Bearing Type & Arrangement	Oversize Series Anti Fiction - Ball / Ball Arrangement
Terminal Box Type & Rating	Oversized Cast Iron Construction - IP66 rating
kW Rating	110
Pole	2
Full Load Speed (Rpm)	2960
Frame Size	280MA
Efficiency @ 100% Loading	96.3
Efficiency @ 75% Loading	95.7
Efficiency @ 50% Loading	94.7
Power Factor @ 100% Loading	90.0
Power Factor @ 75% Loading	88.0
Power Factor @ 50% Loading	82.0
Full Load Current (Amps)	177.00
Starting Current in % (DOL)	763
Starting Current (Amps) (DOL)	1350.5
Full Load Torque (Nm)	355.00
Locked Rotor Torque (DOL) (% of Full Load Torque)	132
Pull Up Torque (DOL) (% of Full Load Torque)	112
Breakdown Torque (% of Full Load Torque)	253
Rotor Inertia in $GD^2/4$ (kG-m ²)	0.8000
Maximum Inertia in $GD^2/4$ (kG-m ²)	8.0800
Noise Pressure Level @ 1 Metre No Load (dBA)	80
Approx. Weight (kG)	720

DOL Torque versus Speed & Current Curve



Efficiency & Power Factor Load Curve

