


<b>DATA SHEET ~ TECO MAXe3™ PREMIUM SEVERE DUTY - MEPS HIGH EFFICIENCY</b>	
Type	Squirrel Cage Induction Motor ~ TEFC
Input Supply	415Volts 50Hz 3 Phase
Degree of Protection	IP66 Complete with Porous Drain Plugs
Mounting Arrangments	IM1001 B3 / IM3001 B5 / IM2001 B35
Cooling Class	IC411
Insulation	Class 'F' 155°C
Temperature Rise	≤80°C
Ambient Condition	40°C (TECO can accept up to 55°C ambient as standard)
Altitude	Less than 1000 Metres above sea level
Application	Vee Belt Drive or Direct Coupled
Starting Method	DOL, Soft Starter or VVVF Duty (Subject to load demand)
Service Factor	1.0 p.u @ Class B Temp. rise - 1.15 p.u @ Class F Temp. rise
Rotation	Bi Directional - Low Noise
Bearing Type & Arrangement	Oversize Series Anti Fiction - Ball / Roller Arrangement
Terminal Box Type & Rating	Oversized Cast Iron Construction - IP66 rating
kW Rating	110
Pole	6
Full Load Speed (Rpm)	985
Frame Size	315MC
Efficiency @ 100% Loading	96.5
Efficiency @ 75% Loading	96.0
Efficiency @ 50% Loading	95.3
Power Factor @ 100% Loading	86.0
Power Factor @ 75% Loading	83.0
Power Factor @ 50% Loading	76.5
Full Load Current (Amps)	184.00
Starting Current in % (DOL)	734
Starting Current (Amps) (DOL)	1350.6
Full Load Torque (Nm)	1068.00
Locked Rotor Torque (DOL) (% of Full Load Torque)	110
Pull Up Torque (DOL) (% of Full Load Torque)	99
Breakdown Torque (% of Full Load Torque)	242
Rotor Inertia in $GD^2/4$ (kG-M <sup>2</sup> )	5.1700
Maximum Inertia in $GD^2/4$ (kG-M <sup>2</sup> )	120.0000
Noise Pressure Level @ 1 Metre No Load (dBA)	73
Approx. Weight (kg)	1180

### DOL Torque versus Speed & Current Curve



### Efficiency & Power Factor Load Curve

