



DATASHEET

TECO MAX-Ex (Exe,ExnA,ExtD)

MOTOR SERIES	TECO MAX-Ex (Exe,ExnA,ExtD)	
START METHOD		DIRECT ONLINE
KW RATING		0.37
VOLTAGE	(V)	240
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		2
FRAME		71
SPEED		
SYNCHRONOUS	(rpm)	3000
FULL LOAD	(rpm)	2800
CURRENT		
FULL LOAD	(Amps)	1.4
LOCKED ROTOR	%	593
TORQUE		
FULL LOAD TORQUE	(Nm)	1.26
STARTING TORQUE	%	352
MINIMUM TORQUE	%	297
BREAKDOWN TORQUE	%	341
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.0008
EFFICIENCY		
100% LOAD	%	75
75% LOAD	%	74
50% LOAD	%	70
POWER FACTOR		
100% LOAD	%	85
75% LOAD	%	78
50% LOAD	%	64
INSULATION CLASS		F/H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	12
BEARINGS		
DRIVE END		6202 ZZ C3
NON DRIVE END		6202 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	54
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C