



DATASHEET

TECO MAX-Ex (Exe,ExnA,ExtD)

MOTOR SERIES	TECO MAX-Ex (Exe,ExnA,ExtD)	
START METHOD		DIRECT ONLINE
KW RATING		0.37
VOLTAGE	(V)	240
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		71
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1405
CURRENT		
FULL LOAD	(Amps)	1.73
LOCKED ROTOR	%	530
TORQUE		
FULL LOAD TORQUE	(Nm)	2.51
STARTING TORQUE	%	357.5
MINIMUM TORQUE	%	297
BREAKDOWN TORQUE	%	335.5
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.0013
EFFICIENCY		
100% LOAD	%	74.5
75% LOAD	%	73
50% LOAD	%	68.5
POWER FACTOR		
100% LOAD	%	69.5
75% LOAD	%	60.5
50% LOAD	%	48
INSULATION CLASS		F/H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	13
BEARINGS		
DRIVE END		6202 ZZ C3
NON DRIVE END		6202 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	50
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C