



DATASHEET

TECO MAX-Ex (Exe,ExnA,ExtD)

MOTOR SERIES	TECO MAX-Ex (Exe,ExnA,ExtD)	
START METHOD		DIRECT ON LINE
KW RATING		0.75
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		80
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1440
CURRENT		
FULL LOAD	(Amps)	1.66
LOCKED ROTOR	%	783
TORQUE		
FULL LOAD TORQUE	(Nm)	4.97
STARTING TORQUE	%	324.5
MINIMUM TORQUE	%	286
BREAKDOWN TORQUE	%	412.5
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.003
EFFICIENCY		
100% LOAD	%	84.5
75% LOAD	%	82
50% LOAD	%	79
POWER FACTOR		
100% LOAD	%	74.5
75% LOAD	%	65
50% LOAD	%	50.5
INSULATION CLASS		F/H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	20
BEARINGS		
DRIVE END		6204 ZZ C3
NON DRIVE END		6204 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	44
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C