



DATASHEET

TECO MAX-Ex (Exe,ExnA,ExtD)

MOTOR SERIES	TECO MAX-Ex (Exe,ExnA,ExtD)	
START METHOD		DIRECT ON LINE
KW RATING		4
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		8
FRAME		160M
SPEED		
SYNCHRONOUS	(rpm)	750
FULL LOAD	(rpm)	720
CURRENT		
FULL LOAD	(Amps)	9.06
LOCKED ROTOR	%	607
TORQUE		
FULL LOAD TORQUE	(Nm)	53
STARTING TORQUE	%	209
MINIMUM TORQUE	%	187
BREAKDOWN TORQUE	%	275
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.086
EFFICIENCY		
100% LOAD	%	87.1
75% LOAD	%	86
50% LOAD	%	84.5
POWER FACTOR		
100% LOAD	%	70.5
75% LOAD	%	62
50% LOAD	%	48.5
INSULATION CLASS		F/H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	133
BEARINGS		
DRIVE END		6309 ZZ C3
NON DRIVE END		6307 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	51
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C