



DATASHEET

TECO MAX-Ex (Exe,ExnA,ExtD)

MOTOR SERIES	TECO MAX-Ex (Exe,ExnA,ExtD)	
START METHOD		DIRECT ON LINE
KW RATING		5.5
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		4
FRAME		132S
SPEED		
SYNCHRONOUS	(rpm)	1500
FULL LOAD	(rpm)	1460
CURRENT		
FULL LOAD	(Amps)	9.83
LOCKED ROTOR	%	916
TORQUE		
FULL LOAD TORQUE	(Nm)	35.9
STARTING TORQUE	%	275
MINIMUM TORQUE	%	225.5
BREAKDOWN TORQUE	%	352
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	0.033
EFFICIENCY		
100% LOAD	%	91
75% LOAD	%	90.5
50% LOAD	%	90.5
POWER FACTOR		
100% LOAD	%	85.5
75% LOAD	%	81
50% LOAD	%	72
INSULATION CLASS		F/H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	75
BEARINGS		
DRIVE END		6308 ZZ C3
NON DRIVE END		6306 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	55
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C