



DATASHEET

MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

MOTOR SERIES	MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
START METHOD			DIRECT ON LINE
KW RATING			0.75
VOLTAGE	(V)		240
PHASES			3
FREQUENCY	(Hz)		50
NO OF POLES			8
FRAME			100L
SPEED			
	SYNCHRONOUS	(rpm)	750
	FULL LOAD	(rpm)	700
CURRENT			
	FULL LOAD	(Amps)	3.93
	LOCKED ROTOR	%	441
TORQUE			
	FULL LOAD TORQUE	(Nm)	10.23
	STARTING TORQUE	%	258.5
	MINIMUM TORQUE	%	242
	BREAKDOWN TORQUE	%	253
ROTOR INERTIA (J = GD²/4)		(Kgm ²)	0.0011
EFFICIENCY			
	100% LOAD	%	76.6
	75% LOAD	%	76.5
	50% LOAD	%	73
POWER FACTOR			
	100% LOAD	%	60
	75% LOAD	%	50.5
	50% LOAD	%	38.5
INSULATION CLASS			F
ENCLOSURE TYPE			TEFC
IP RATING			66
WEIGHT OF MOTOR		kgs	39
BEARINGS			
	DRIVE END		6206 ZZ C3
	NON DRIVE END		6305 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M		dbA	49
DESIGN STANDARD			AS1359
CERTIFICATION			
TEMPERATURE RISE ABOVE AMBIENT			< 80 DEG C