



DATASHEET

TECO MAX-Ex (Exe,ExnA,ExtD)

MOTOR SERIES	TECO MAX-Ex (Exe,ExnA,ExtD)	
START METHOD		DIRECT ON LINE
KW RATING		132
VOLTAGE	(V)	415
PHASES		3
FREQUENCY	(Hz)	50
NO OF POLES		2
FRAME		315SA
SPEED		
SYNCHRONOUS	(rpm)	3000
FULL LOAD	(rpm)	2976
CURRENT		
FULL LOAD	(Amps)	211
LOCKED ROTOR	%	754
TORQUE		
FULL LOAD TORQUE	(Nm)	423
STARTING TORQUE	%	126.5
MINIMUM TORQUE	%	107.8
BREAKDOWN TORQUE	%	242
ROTOR INERTIA (J = GD²/4)	(Kgm ²)	1.275
EFFICIENCY		
100% LOAD	%	96.6
75% LOAD	%	95.7
50% LOAD	%	94.9
POWER FACTOR		
100% LOAD	%	90
75% LOAD	%	88
50% LOAD	%	82
INSULATION CLASS		F/H
ENCLOSURE TYPE		TEFC
IP RATING		66
WEIGHT OF MOTOR	kgs	900
BEARINGS		
DRIVE END		6314 C3
NON DRIVE END		6314 C3
NO LOAD SOUND PRESSURE LEVEL @ 1M	dbA	85
DESIGN STANDARD		AS1359
CERTIFICATION		
TEMPERATURE RISE ABOVE AMBIENT		< 80 DEG C