



DATASHEET

MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW

MOTOR SERIES	MAX-E3 PREMIUM SEVERE DUTY Totally Enclosed Fan-Cooled Cast Iron Frame to 185kW		
START METHOD			DIRECT ON LINE
KW RATING			3
VOLTAGE	(V)		240
PHASES			3
FREQUENCY	(Hz)		50
NO OF POLES			2
FRAME			100L
SPEED			
	SYNCHRONOUS	(rpm)	3000
	FULL LOAD	(rpm)	2870
CURRENT			
	FULL LOAD	(Amps)	9.27
	LOCKED ROTOR	%	932
TORQUE			
	FULL LOAD TORQUE	(Nm)	9.97
	STARTING TORQUE	%	390.5
	MINIMUM TORQUE	%	363
	BREAKDOWN TORQUE	%	412.5
ROTOR INERTIA (J = GD²/4)		(Kgm ²)	0.006
EFFICIENCY			
	100% LOAD	%	88.5
	75% LOAD	%	88.5
	50% LOAD	%	87
POWER FACTOR			
	100% LOAD	%	88
	75% LOAD	%	85
	50% LOAD	%	76
INSULATION CLASS			F
ENCLOSURE TYPE			TEFC
IP RATING			66
WEIGHT OF MOTOR		kgs	39
BEARINGS			
	DRIVE END		6206 ZZ C3
	NON DRIVE END		6305 ZZ C3
NO LOAD SOUND PRESSURE LEVEL @ 1M		dbA	57
DESIGN STANDARD			AS1359
CERTIFICATION			
TEMPERATURE RISE ABOVE AMBIENT			< 80 DEG C