

1110987654321

POLE		HP	kW	Hz	VOLT	r/min(RPM)	INS	RATING	DIMENSION IN		APPROX WEIGHT	BEARINGS	
4		F	CONT.	mm			DE:NU318C3	NDE:6318C3

G

8— ϕ 18.5
HOLES

45°

588

F

E

D

M50XP1.5+2~M20XP1.5

425

30

1019

849

170

5

22

140

ϕ 550
 ϕ 450
+0.063

375

GROUNDING
TERMINAL

22

85

71

ϕ 80m6

M20 TAP

DEEP 40

B

OUTLINE DIMENSIONS

3—PHASE INDUCTION MOTOR

- NOTE:
- FOR DIRECT FLEXIBLE COUPLING
 - ENCLOSURE: IP56 PROTECTION
 - Ex db IIB T4 Gb & Ex db I Mb (IECEx/ATEX)
 - NON-SPARKING FAN
 - WITH THERMISTOR
 - WITH SPACE HEATER
 - WITH BEARING RTD
 - FITTED WITH SPM ADAPTER
 - THIS DRAWING IS PRELIMINAL FOR REFERENCE

A

MOTOR TYPE	AEMVXZ	FRAME NO.	280SC
CUSTOMER	.	DATE	
ORDER NO.	.	TRANS. SHEET	.

第三角法

APPD.	徐聰豪	11.10.21	東元電機股份有限公司 TECO Electric & Machinery Co., Ltd. TAIWAN	DWG NO.	
CHKD.	陳奕元	11.10.21		31057C463270	
DWG.	陳奕元	11.10.21			

11

9

8

7

6

5

4

3

2

1

2