

1110987654321

POLE		HP	kW	Hz	VOLT	r/min(RPM)	INS	RATING	DIMENSION IN		APPROX WEIGHT	BEARINGS	
4		F	CONT.	mm			DE:NU318C3	NDE:6318C3

G

8— ϕ 18.5
HOLES

45°

588

30

ϕ 500

425

M50XP1.5+2~M20XP1.5

1069

899

170

5

22

140

ϕ 550
 ϕ 450
+0.063

375

GROUNDING
TERMINAL

22

85

71

+

M20 TAP

DEEP 40

B

OUTLINE DIMENSIONS

3—PHASE INDUCTION MOTOR

MOTOR TYPE	AEMVXZ	FRAME NO.	280MC
CUSTOMER	.	DATE	
ORDER NO.	.	TRANS. SHEET	.

A

NOTE:
1. FOR DIRECT FLEXIBLE COUPLING
2. ENCLOSURE: IP56 PROTECTION
3. Ex db IIB T4 Gb & Ex db I Mb (IECex/ATEX)
4. NON-SPARKING FAN
5. WITH THERMISTOR
6. WITH SPACE HEATER
7. WITH BEARING RTD
8. FITTED WITH SPM ADAPTER
9. THIS DRAWING IS PRELIMINAL FOR REFERENCE

第三角法

東元電機股份有限公司
TECO Electric & Machinery Co., Ltd.

DWG NO.

31057C464360

TAIWAN

11

9

10

8

7

6

4

3

2

1

2